

FUEL DISPENSING HOSE



NEOGI FUEL DISPENSING HOSE IS DESIGNED AND ENGINEERED SPECIFICALLY FOR CONSTANT CONTACT USE IN THE TRANSFER OF REFINED FUELS (COMMERCIAL GASOLINE AND DIESEL FUEL), OILS AND OTHER PETROLEUM PRODUCTS, ALTERNATIVE FUELS SUCH AS BIO-DIESEL, BIO-DIESEL BLENDS, ETHANOL AND ETHANOL BLENDS. IT IS IDEAL FOR TANK TRUCK, TERMINAL LOADING AND IN-PLANT OPERATIONS.

NEOGI FUEL DISPENSING HOSE FEATURES

NAME OF THE PRODUCT :	FUEL DISPENSING HOSE (HOSE PIPE)
BRAND :	NEOGI
AVAILABLE VARIANT :	1 INCH (25MM) & 3/4 INCH (19MM)
BODY MATERIAL :	SYNTHETIC RUBBER
REINFORCEMENT :	HIGH STRENGTH STEEL WIRE BRAID
TEMPERATURE RANGE :	- 40°C TO + 55°C
WORKING PRESSURE :	16 BAR
APPLICATION :	DISPENSING PETROLEUM PRODUCTS
APPLICABLE STANDARD :	BS EN 1360:2013 TYPE I GRADE Q BS EN 1360:2013 TYPE III GRADE M
COLOUR :	BLACK



NEOGI TECHNOLOGIES AND RESEARCH PRIVATE LIMITED

(C.I.N. : U93000WB2013PTC192588)

AN IMS Certified Organisation

Regd. off: 2, Kumarpara Road, P.O. : Rajpur, Kolkata - 700 149, West Bengal, India

Phone : +91 33 3544 1839 | Mob : +91 98307 05545

E-mail : support@ntrindia.co.in | Visit us : www.ntrindia.co.in

